GHISARREDO
LIGHT AND DESIGN

LPC 011 POLE - TECHNICAL DATA

1:20 SCALE



LPC 200
Optional base

LPC 011 F
Pole with **F**lange

LPC 011 M
Pole with **M**asonry

DESCRIPTION

STRUCTURE

S235JR steel pole (UNI EN 10025).
Ø102 mm hot-dip galvanized according to standards (UNI EN ISO 1461).

Optional cast aluminum base.
(UNI EN 1706) Ø360 mm.

Cast aluminum fitting
(UNI EN 1706) Ø102-60 mm.

Threaded ¾ end sleeve in steel cold-dip galvanized.

Die-cast aluminum hatch.

Stainless steel hardware.

For details of ground anchorage, refer to the technical drawing.

PAINTING CYCLE

STEEL
Coat of two-component zinc phosphate primer and two coats of finish with two-component standard gray (S) paint. RAL colors on request.

ALUMINIUM
Pickling and washing with water demineralized, nanotechnological process, drying at 160°C. Polyester powder primer coat and oven curing at 200°C.
Finishing coat with two-component varnish standard gray color (S).
RAL colors on request.

GHISARREDO srl - Via Biagio di Santolino 86 - 47892 Acquaviva - Repubblica di San Marino
Tel. +378 0549 999675 Fax +378 0549 911563 C.o.E. Sm22872
www.ghisarredo.com - info@ghisarredo.com